

# R48

## Standard tube for fastening of membranes in the overlap

- To combine with a  $\varnothing$  4,8 to 6,8 mm screw
- Length 20mm to 730mm
- Modified PP
- Size  $\varnothing$  48 mm
- From length 40 mm till 210 mm, this tube is also available in Large Nose (LN) edition, for the perfect combination with the LBS  $\varnothing$  8,0 mm screw
- ASTL for tapered insulation: see Concrete deck
- ETA approval 08/0285
- Sintef approval 2516



## Products

PRODUCT CODE	$\varnothing$ MM X LENGTH MM	PACKAGING
1715409	R48-020, 48 X 20mm	1500
1715410	R48-040, 48 X 40mm	1500
1715411	R48-060, 48 X 60mm	1500
1715412	R48-080, 48 X 80mm	1500
1715413	R48-090, 48 X 90mm	1500
1715432	R48-100, 48 X 100mm	1000
1715433	R48-120, 48 X 120mm	1000
1715434	R48-150, 48 X 150mm	750
1715435	R48-180, 48 X 180mm	500
1715436	R48-210, 48 X 210mm	500
1715437	R48-240, 48 X 240mm	250
1715438	R48-270, 48 X 270mm	250
1715439	R48-300, 48 X 300mm	250
1715440	R48-330, 48 X 330mm	250
1715441	R48-430, 48 X 430mm	250
1715442	R48-530, 48 X 530mm	250
1715445	R48-630, 48 X 630mm	250
1715447	R48-730, 48 X 730mm	250

## Associated products



### **BS 4,8 (FM Approval)**

For use with BIT-T25  
TX 25 head  
Ø 4,8 mm



### **CS 6,1 (FM Approval)**

Pre-drill: Ø 5,0 mm. In hard  
concrete 5,2 mm  
TX 25 head  
Hi-lo thread



### **LBS 6,0**

TX 25 head  
S-Point  
Length: 60 to 240 mm



### **PS 4,8**

For use with BIT-T25  
TX 25 head  
Ø 4,8 mm