

CS 6,1 (FM APPROVAL)

Screw for use in concrete

Required length:

Build up + 25 mm (CS-61028 to CS-61100)

Build up + 30 mm (CS-61110 to CS-61280)

Screw length from 28 up to 100 mm with blunt point

Screw length from 120 up to 280 mm with sharp point

Pre-drill: \varnothing 5,0 mm. In hard concrete 5,2 mm

Note: pull-out test is recommended

Approvals

- Sintef technical approval 2516
- ETA approval 08/0285
- FM approval ID-Nr.3034551
- FM approval ID-Nr.3060559



Size

\varnothing 6,1 mm

Material

Carbon steel

Screw

Hi-lo thread

Torx-25 head

Enduroguard coating

15 cycli

Length

From 28 to 280 mm

Products

PRODUCTCODE	\varnothing MM X LENGTH MM	PACKAGING
1413047	CS-61028, 6,1 X 28 mm	1000/Bucket
1413048	CS-61040, 6,1 X 40 mm	1000/Bucket
1413049	CS-61050, 6,1 X 50 mm	1000/Bucket
1413050	CS-61060, 6,1 X 60 mm	1000/Bucket
1413051	CS-61070, 6,1 X 70 mm	500/Bucket
1413052	CS-61080, 6,1 X 80 mm	500/Bucket
1413053	CS-61090, 6,1 X 90 mm	500/Bucket
1413054	CS-61100, 6,1 X 100 mm	500/Bucket
1413055	CS-61120, 6,1 X 120 mm	500/Bucket
1413056	CS-61140, 6,1 X 140 mm	500/Bucket
1413057	CS-61160, 6,1 X 160 mm	500/Bucket
1413058	CS-61180, 6,1 X 180 mm	500/Bucket
1413059	CS-61200, 6,1 X 200 mm	500/Bucket
1413060	CS-61220, 6,1 X 220 mm	500/Bucket
1413061	CS-61240, 6,1 X 240 mm	500/Bucket
1413062	CS-61260, 6,1 X 260 mm	500/Bucket
1413063	CS-61280, 6,1 X 280 mm	500/Bucket

Associated products



Drills & Extenders

Tools for fastening



Ergodrill

Accessory for drilling in an upright position.

Alternative products



BN 5,6

Pre-drill: \varnothing 5,00 mm
Length: from 28 to 160 mm



CP50 Concrete plug

Coated nail
Length: from 75 to 215 mm